

ATELIER

BY DUCHATEAU

ATELIER SERIES

SOLSTICE



PRODUCT ID	ATL-SLTC7-31 ATL-SLTC9-31	LENGTH	RANDOM LENGTH UP TO 96.5" (2450 MM)	THICKNESS	5/8" (15 MM)
SPECIES	EUROPEAN OAK	CONSTRUCTION	ENGINEERED	INSTALLATION	GLUE-DOWN, NAIL/STAPLE, WITH GLUE-ASSIST OR FLOATING ²
SURFACE LAYER	4 MM ¹	GRADE	CHARACTER	RADIANT HEAT	APPROVED (See installation instructions)
PLANK WIDTHS	7.5" (190 MM) 9.5" (240 MM)	FINISH	UV OIL	TRIM	STAIRNOSE, REDUCER, THRESHOLD, T-MOLD, AND SQUARENOSE
COVERAGE PER BOX	7.5": 20.04 SQ. FT., 9.5": 25.32 SQ. FT.	SHEEN	MATTE	WARRANTY	LIMITED LIFETIME STRUCTURAL INTEGRITY 25-YEAR RESIDENTIAL SURFACE FINISH 3-YEAR COMMERCIAL SURFACE FINISH
		SURFACE TREATMENT	WIRE-BRUSHED		

RELATIVE HUMIDITY (in %)



VARIATION GUIDE



This bar shows examples of the natural variation and graining you should expect with this flooring.

DUCHATEAU.COM | 1.888.DUCHATEAU

Product Sample Disclaimer: DUCHATEAU's collections reflect a love for the natural beauty of wood, each product expressing distinct variations in size, shape, thickness, finish, texture, grain, and overall character. It is our celebration of the nuances that create unique variation in every plank. Individual samples of these floors are intended as reference, rather than exact representations, of the entire range of color variation and character that will be present in the flooring you will receive. To better understand the unique look of DUCHATEAU finished floor in your space, we recommend consulting your Sales Representative.

Installation and Performance Disclaimer: Environmental conditions, such as exposure to light, and fluctuations in temperature and humidity, can affect product performance from initial installation throughout its life. Refer to our website for installation guidelines or see your local Sales Representative for more information on successfully installing, caring for, and ensuring the lifelong performance of your floor.

Note: All measurements are nominal.

¹ - Nominal wear layer thickness measured prior to finishing processes such as wire-brushing will affect the overall thickness.

² Flooring with plank widths above 7.5" cannot be floated. 171 TSCA Title VI Compliant.

©DUCHATEAU | All rights reserved.



ATL-SLTC9-SB